

### APPLICATIONS

UL) us

Ideal for **7 Day** control: Lighting, signs, pumps, motors, fans, heating & air-conditioning, security systems.





#### **FEATURES**

- AUTOMATIC input voltage detection
- 7 ON and OFF pairs for programs on each day of the week
- Daylight Savings: Quick button for one hour adjustment
- Power Outage Backup:
- BATTERY RETAINS TIME and schedule
- 4-in-1 DPDT Contacts include SPST, SPDT, DPST
- LED INDICATORS Red for load status, Green for power
- 40 AMP contact
- Manual Override ON & OFF

# SPECIFICATIONS

#### **MULTI-VOLTAGE INPUT:**

120/208-240/277VAC (automatic detection) OPERATING TEMPERATURE: -31 °F to 116 °F (-35 °C to 47 °C) ENCLOSURE: Indoor/Outdoor NEMA 3R plastic





40A Resistive @ 120-277VAC 30A Inductive @ 120-277VAC 1HP, 30FLA, 90LRA @ 120VAC 2HP, 20FLA, 60LRA @ 240VAC 30A Ballast @ 120VAC 20A Ballast @ 277VAC 15A Tungsten @ 120VAC 20A @ 28VDC 720VA Pilot Duty @ 120-240VAC 30A Max above 104 °F

# NC CONTACTS:

30A Resistive @ 120-277VAC 15A Inductive @ 120-277VAC 1/4HP, 12 FLA, 30LRA @ 120VAC 1/2HP, 12FLA, 33LRA @ 240VAC 10A Ballast @ 120-277VAC 290VA Pilot Duty @ 120VAC 360VA Pilot Duty @ 240VAC

RATINGS



UNIVERSAL MULTI-VOLTAGE

