

APPLICATIONS



Ideal for **7 Day** control of water heaters. Turn OFF when no one is home or when rates are high.



**DETECTS
INPUT
VOLTAGE
AUTOMATICALLY!**

FEATURES

- **AUTOMATIC** input voltage detection
- 7 ON and OFF pairs for programs on each day of the week
Daylight Savings: quick button for one hour adjustment
- Power Outage Backup:
BATTERY RETAINS TIME and schedule
- **4-in-1** DPDT Contacts include SPST, SPDT, DPST
- **LED INDICATORS** - red for load status, green for power
- 40AMP contact
- External manual override ON and OFF

SPECIFICATIONS

MULTI-VOLTAGE INPUT:

120/240VAC, 50/60Hz (automatic detection)

TERMINAL RANGE:

#8-#18AWG

OPERATING TEMPERATURE:

-31 °F to 116 °F (-35 °C to 47 °C)

POWER CONSUMPTION:

6VA maximum

ENCLOSURE:

polycarbonate indoor NEMA 1 enclosure with clear cover



RATINGS

NO CONTACTS:

40A Resistive @ 120-277VAC
30A Inductive @ 120-277VAC
1HP, 30FLA, 90LRA @ 120 VAC
2HP, 20FLA, 60 LRA @ 240VAC
30A Ballast @ 120VAC
20A Ballast @ 277VAC
15A Tungsten @ 120VAC
20A @ 28VDC
720VA Pilot Duty @ 120-240VAC
30A Max above 104 °F

NC CONTACTS:

30A Resistive @ 120-277VAC
15A Inductive @ 120-277VAC
1/4HP, 12 FLA, 30LRA @ 120VAC
1/2HP, 12FLA, 33LRA @ 240VAC
10A Ballast @ 120-277 VAC
290VA Pilot Duty @ 120VAC
360VA Pilot Duty @ 240 VAC

