

FireStop™ Offering

• FireStop™ Intumescent Caulk

is water-based, single component elastomeric sealant intended for use as a firestop system component. It forms an economical yet durable, flexible and watertight bond with most construction materials.

• FireStop814[™] Caulk

FireStop814[™] Fire stopping caulk is a single component, non-combustible, non-intumescent material for residential and commercial applications. Colored red for easy inspection, FireStop814 creates an effective barrier against flames, smoke, and toxic gasses and has superior adhesion and gunnability.

• FireBlok 136[™] Caulk

FireBlock136[™] Fire-blocking caulk is a single component, noncombustible material for residential applications. FireBlock136 is for use in annular spaces around wires, pipes, ducts, vents and other penetrating items at ceiling and floor openings; and room to room in wood and steel frame constructions.

• Fire Rated Putty Pads

NSi Fire Rated Putty is a moldable non-curing, one-component fire rated material for through penetration fire stop systems. In the event of a fire, Putty will expand when exposed to fire, forming an insulating char, which prevents the spread of flames, smoke, gas and water through penetration openings. Installation is easy as there are no additives, there is no mixing and no curing time is required. The putty is applied by hand and adheres to all common building surfaces.

• FireStop8136[™] Pillows

FireStop[™] Pillows are a single step firestop system component. Intended for wall and/or floor openings through fire separations where temporary or permanent firestops are required. They are ideal where cable retrofitting is frequent and anticipated. Quick and clean single product installation.



NSi Industries, LLC USA • 800.321.5847 www.nsiindustries.com

